

# RF DC Block Protector, 698-2700 MHz, Type N F-F

### **DCB-COM-NFF**



#### • DCB-COM-NFF

N Female Connectors on Surge and Protected Side

The DCB series surge arrestor is a RF broadband device designed for surge and lightning protection applications where DC Block is required. A DC Blocking device with its internal series capacitor circuit. This DCB unit offers excellent surge / lightning suppression for telecommunications systems.

The DCB series demonstrates excellent RF characteristics while offering outstanding surge protection.

#### **FEATURES:**

- Broad Band Design
- Excellent Insertion Loss and Return Loss Characteristics Over Frequency Range
- DC Block
- Multi-Strike Capability
- Surge Current of 40kA
- Max Power 750W RMS
- RoHS & CE Compliant
- Bulkhead Mounting
- IP67 Rated

#### **APPLICATIONS:**

- Public Safety Systems
- 4G/5G Cellular Systems
- Emergency Response Systems
- Other Wireless Applications that Require DC Block to Equipment

RF Specifications		
Impedance	50 Ω	
Frequency	698 – 2700 MHz	
VSWR/Return Loss (Over Frequency)	≤1.15:1 Max / 23.1 dB	
Insertion Loss (Over Frequency)	≤0.2dB to ≤2700 MHz	
Maximum RF Power	750W RMS Average	

Transient Specifications			
<b>Protection Circuit</b>	DC Block		
Surge Current	IEC 61000-4-5 8/20µs Waveform		
Maximum Surge	50 kA (1x)		
Multi-Strike	20 kA Multiple (10x)		
Let-Through Energy	≤10µJ ±20% @ 20kA 8/20µs Waveform		
Let-Through Voltage	≤10VDC ±20% @20kA 8/20µs Waveform		




# RF DC Block Protector, 698-2700 MHz, Type N F-F

Mechanical / Environmental Specifications				
Storage / Operational Temp	-50°C to +85°C			
Ingress Protection	IP67 IEC 60529			
Bellcore	TA-NWT-000487			
Weight	5.2 oz (147.4 g)			
RoHS Compliant	Yes			
CE	Yes			

Material & Finish Specifications				
Component	Material	Finish		
<b>Outer Parts</b>	Aluminum	Ball Burnish		
Connectors	Brass	Tri-Metal		
Coupling Nut & Washer	SST			
<b>Center Contact</b>	Be Cu / Brass	Gold		
Insulator	PTFE			

## **Mechanical Outlines**



# **O**

#### Hardware Kit Included

Item	Description	Qty
1	5/8"-24 HEX NUT	1
2	5/8" INTERNAL LOCK WASHER	1
3	'O'-RING 019 SILICONE	1
4	SCREW CAP M8 X 1.25 X 10mm	1
5	5/16" EXT TOOTH LOCK WASHER 18-8 SS	1